THOMSON

DPL 909 VD

Thomson Home Cinema DVD Pack

FEATURES	BENEFITS
Extra - slim design thanks to Digital amplifier technology	For better home integration when space is limited
DVD/DVD+R/CD/-R/-RW/mp3/VCD/S-VCD player compatible With Digital Photoview JPEG&Kodak pictures	The real home cinema package to watch your favorite movies, pictures, listen to music
360 W total output power	The five speakers and the subwoofer deliver dynamic and rich Home cinema sound
Scart RGB connection	Plug easily TV or VCR and get optimal image quality
DPL II / Dolby Digital / DTS decoders	Enjoy superior multi - channel digital audio sound

THOMSON

DPL 909 VD

Technical data:

BRAND	
Brand	THOMSON
TUNER	
Tuner type	Digital
Presets	30
FM frequency	87.5 MHz - 108 MHz
MW frequency	522 - 1620 kHz
LW frequency	-
R.D.S. / EON	Yes/-
R.D.S. functions	Station name
Scanning system	manual + auto
Memory system	manual + auto
AMPLIFIER	
Amplification type	Digital
DPL / DPL II	Yes / -
DD / DTS	Yes / Yes
Total output power (RMS)	200
Left / Right output power (2x)	2 x 30
Center output power (1x)	30
Left / Right Rear output power (2x)	2 x 30
Subwoofer output power	50
THD (%)	10
Surround Sound	Yes
Equalizer presets	-
DSP	-
Mute on / off	Yes
Volume control	Digital control : rotary
Sound enhancement	-
Mode	-
Test signal	Yes
Jog shuttle	-
DVD PLAYER	
Dolby Prologic / DPL II	Yes / -
DD / DTS	Yes / yes
DVD video/CD Audio/VCD/S-VCD/DVD+R	Yes/Yes/Yes/Yes/Yes
CD-R / CD-RW / MP3 compatibility/JPEG	Yes/Yes/Yes/Yes
SACD compatible	-
DVD audio ready	-
Region code	2
Slow motion Playback	Yes
Frame advance (forward / reverse)	Yes
Quick search (forward / reverse)	Yes
Fine still picture	Yes
Zoom function	x2, x4, x8
Progressive Scan	-
A-B Playback (disc, chapter, title)	-
Program delay	Yes
Parental control	Yes
Mark function	-
SPEAKERS BOX	
LEFT / RIGHT SPEAKERS	
way number	1
impedance (Ohms)	8
power efficiency (W)	30
magnetically shielded	yes
connexion	clips
wall mounted	yes
CENTER SPEAKERS	
way number	1
impedance (Ohms)	8
power efficiency (W)	30
magnetically shielded	yes
connexion	clips
wall mounted	yes
REAR SPEAKERS	
way number	1
impedance (Ohms)	8
power efficiency (W)	30
magnetically shielded	yes
connexion	clips
wall mounted	yes
SUBWOOFER	
passive / active	yes / -
speaker drivers	6.5"
frequency range	40 Hz - 160 Hz
CONNECTION / POWER SUPPLY	
AC power	230 V / 50 Hz
SCART	1 RGB
SUB OUT	yes
Audio IN / Audio OUT	2 / 1
Video IN / Video OUT	- / 1
S-Video IN / OUT	0 / 1
Digital IN (coaxial / optical)	- / -
Digital OUT (optical)	-
Main speaker connection	Clips
Surround connections	Clips
Headphone Jack	3.5 mm
FM / AM Antenna	Yes / -
USER INTERFACE	
Display type	VFD
Display color	Green
Backlit display	Yes
Dimmer (nber steps)	TBC
Sleep Timer (min)	120
Clock	-
Wake-Up Mode	-
Help mode	-
CD Text	-
Panel Control	-
Remote control	I / R Remote Control
OSD (languages)	5
COLOUR	
Color	Silver
GENERAL DATA	
Power cable	Pluggable
Power consumption (1/8 rating power/ Ma	220 W
Standby power consumption	<3W
Size main unit (WxHxD) mm / Weight	430 x 60 x 372
Size subwoofer (WxHxD) mm/ Weight	160 x 350 x 356
Size center speaker (WxHxD) mm/ Weight	88 x 130 x 100
Size L&R and surround (WxHxD) mm /Weight	88 x 130 x 100
Size packaging (WxHxD) in mm	645 x 330 x 445
EAN 13 code	3244480123744
Weight (net/gross) in kg	14 / 14.8
ACCESSORIES	
Cables	Speakers, Composite Video Cable
Antenna	FM cable
Batteries	AA type x 2